

STAINLESS STEEL

SSLFHFD-FFU

FAN FILTER UNIT

FILTER OPTIONS						
Unit Size	Type	Flow	Filter Size			Rated CFM
			Width	Height	Depth	
48x24	HEPA	HIGH	43.5	19.5	3.5	1200
48x24	HEPA	STANDARD	43.5	19.5	2.88	900

48x24 HIGH FLOW FILTER, AT 0 STATIC, 208-277VAC				
Setpoint	CFM	CFM/ Sq Ft	Watts	RPM
100%	1320	273	423	2450
90%	1156	239	310	2205
80%	975	202	216	1960
70%	790	163	143	1715
60%	617	128	90	1470
50%	430	89	54	1225
40%	275	57	29	980
30%	162	33	17	735
20%	74	15	10	490

48x24 HIGH FLOW FILTER, AT 0 STATIC, 120VAC				
Setpoint	CFM	CFM/ Sq Ft	Watts	RPM
100%	1074	222	257	2090
90%	917	189	185	1881
80%	760	157	134	1672
70%	608	126	86	1463
60%	450	93	55	1254
50%	312	64	33	1045
40%	200	41	20	836
30%	114	24	13	627
20%	51	11	9	418



8701 Elmwood Ave #400
Kansas City, MO 63132
Ph:816-231-5522 Fax:816-231-8437
800-247-5746 Email:robhaake@ajmfg.us
Please Visit Our Web Site At: www.ajmfg.com

DRAWN SLG	MATERIAL	JOB NAME SSLFHFDFDU PERFORMANCE DATA	TAG	QTY	REV #
CHKD RH	FINISH	ENGINEER	DRAWING NAME		SHT 1/3
APRVD	SIZE 48 x 24	CONTRACTOR			SCL 1:1
					DO NOT SCALE